AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Currently amended) A fuel pump comprising an electromotive drive that has a commutator and carbon brushes which brush alternately against commutator segments as the commutator rotates, characterized in that the commutator segments (16, 18) contain graphite and at least one commutator segment (16, 18) contains graphite and an admixture of a material (30) that has a greater hardness than graphite, wherein products of corrosion on running surfaces of the carbon brushes are increased abrasively wearable by the material of greater hardness.
- 2. (Previously presented) The fuel pump as claimed in claim 1, characterized in that the admixture material (30) occurs in the form of individual particles (28) in the graphite.
- 3. (Previously presented) The fuel pump as claimed in claim 2, characterized in that the particles (28) are uniformly dispersed in the respective commutator segments (16, 18).
- 4. (Previously amended) The fuel pump as defined in claim 1, characterized in that the admixture material (30) is aluminum oxide.
- 5. (Previously amended) The fuel pump as defined in claim 1, characterized in that the proportion of admixture material (30) in the respective commutator segments (16, 18) is approximately 0.2%.
- 6. (Previously amended) The fuel pump as defined in claim 1, characterized in that the commutator segments (16, 18) are oriented radially in relation to the

- commutator axis and that the carbon brushes (24, 26) bear axially against the commutator segments (16, 18).
- 7. (Currently amended) The fuel pump as defined in claim 4 or 5, characterized in that the commutator segments are oriented axially in relation to the commutator axis and that the carbon brushes bear radially against the commutator segments.
- 8. (Previously amended) The fuel pump as defined in claim 4, characterized in that all commutator segments (16, 18) coming into contact with the carbon brushes (24, 26) contain the admixture material (30).
- 9. (New) The fuel pump as defined in claim 5, characterized in that the commutator segments are oriented axially in relation to the commutator axis and that the carbon brushes bear radially against the commutator segments.
- 10. (New) The fuel pump as defined in claim 5, characterized in that all commutator segments (16, 18) coming into contact with the carbon brushes (24, 26) contain the admixture material (30).